

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Multi-Seal Tire Sealant-Heavy Duty Environmental Formula

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name MULTI-SEAL® Corporation	Emergency Telephone Number 281-591-0111
Address (Number, Street, City, State and ZIP Code) 16750 Hedgecroft, Suite 512	Telephone Number for Information 281-591-0111
Houston, Texas 77060 USA	Date Prepared 08/17/01
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

OSHA Standards:

This Product is not a "hazardous chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.

SARA 313 Information:

To the best of our knowledge, this product contains no chemical subject to SARA Title III, Section 313 Notification requirements.

SARA Hazard Category Information:

This product does not meet any hazard Category.

Toxic Substances control Act (TSCA) Information:

This product is not required to be listed on the TSCA Inventory.

Section III - Physical/Chemical Characteristics

Boiling Point	Greater than	240°F	Specific Gravity (H ₂ O = 1)	1.1
Vapor Pressure (mm Hg.)		.08mm Hg	Melting Point	N/A
Vapor Density (AIR = 1)	Greater than	1	Evaporation Rate Butyl Acetate = 1)	Greater than 0.01
Solubility in Water	N/A			
Appearance and Odor	Pale green thick liquid.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Greater than 212°F C.O.C.	Flammable Limits	Non-flammable	LEL	UEL
Extinguishing Media	N/A				
Special Fire Fighting Procedures	N/A				
Unusual Fire and Explosion Hazards	None				

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	XX	None

Incompatibility (Materials to Avoid) Strong Oxidizing Agents

Hazardous Decomposition of Byproducts Oxides or carbon, nitrogen and sulfur

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	XX	None

Section VI - Health Hazard Data

Route(s) of Entry Inhalation? Yes Skin? Minimal Ingestion? Yes

Health Hazards (Acute and Chronic) Repeated excessive ingestion may cause central nervous system effects.

Skin: Minimally Irritating

Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?

None

Signs and Symptoms of Exposure Repeated, excessive ingestion: central nervous system effects.

Medical Conditions Generally Aggravated by Exposure None

Emergency and First Aid Procedures: Eyes: Flush with water. If irritation persists, see physician.

Skin: Flush with water. Inhalation: Move to well ventilated area. Ingestion: Get medical attention. Induce vomiting.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken In Case Material is Released or Spilled Use absorbent material to soak up small spills.

Waste Disposal Method Waste material should be disposed of in accordance with local, state and federal regulations.

Precautions to Be Taken in Handling and Storing Maintain good housekeeping practices.

Other Precautions Maintain good housekeeping practices.

Section VIII - Control Measures

Respiratory Protection (Specify Type) None needed. General room ventilation is expected to be adequate.

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves Rubber Gloves Eye Protection Goggles

Other Protective Clothing or Equipment None

Work/Hygienic Practices Maintain good housekeeping practices